

These claims **replace** the claims that were published in the PCT

Please **replace** the claims to read:

**Listing and Amendments to claims**

1. (currently amended) A video display (100) comprising:
  - a controller (131) responsive to a first signal by providing power to a first set of circuits of said display (100);  
said controller (131) responsive to a second signal by removing power from a second set of circuits of said video display (100);  
a timer (135) defining a time interval between an instance of said second signal and an instance of said first signal;  
wherein said first set of circuits is different from said second said of circuits during said time interval.
2. (currently amended) The video display (100) of claim 1 wherein, during said time interval, said first set of circuits excludes a lamp power circuit (106) and said second set of circuits includes said lamp power circuit (106).
3. (currently amended) The video display (100) of claim 2 wherein said lamp power circuit I(106) is coupled to an image lighting lamp (107).
4. (currently amended) The video display (100) of claim 3 wherein said image lighting lamp (107) is a mercury vapor lamp.
5. (currently amended) The video display (100) of claim 2 wherein, outside of said time interval said first set of circuits and said second set of circuits are substantially the same.

6. (currently amended) A video display (100) comprising:

a controller (131) capable of responding to a first signal by energizing a first set of circuits of said display (100);

said controller (131) capable of responding to a second signal by de-energizing a second set of circuits of said display (100);

a timer (135) defining a time interval between an instance of said second signal and an instance of said first signal;

wherein said controller (131) selects members of said first set of circuits based upon a condition of said timer (135).

7. (currently amended) The display (100) of claim 6 wherein said first signal is a power on signal and said second signal is a power off signal.

8. (currently amended) The display (100) of claim 7 wherein said timer (135) comprises a lamp cool down timer for a high intensity discharge lamp (107).

9. (currently amended) The video display (100) of claim 1 wherein both said first set of circuits and said second set of circuits include circuits selected from the group comprising, tuners (161), speakers and amplifiers (162), and audio video (A/V) input circuits (163).

10. (currently amended) The video display (100) of claim 1 wherein said first signal and second signals are provided by a user operable control device (150).

11. (currently amended) A video display system (100) comprising:  
an image lighting lamp (107);  
a control circuit (130) for applying and removing power for said image lighting lamp (107);  
said control circuit (130) including a timer (135);  
said timer (135) commencing a time interval when said control circuit (130) removes power from said image lighting lamp (107);  
said control circuit (130) maintaining said image lighting lamp (107) de-energized during said time interval;  
wherein said control circuit (130) is capable of applying power to circuits of said video display apparatus, other than said image lighting lamp (107), during said time interval.

12. (original) A method for applying power to circuits of a video display, the method comprising the steps of:

applying power to a first set of said circuits in response to a first signal;  
removing power from a second set of said circuits in response to a second signal;  
defining a time interval between an instance of said second signal and an instance of said first signal and during which said first set of circuits is different from said second said of circuits and outside of which, said first set of circuits is the same as said second set of circuits.

14. 13 (currently amended) A method for applying power to circuits of a video display, the method comprising the steps of:

applying power to a first set of said circuits in response to a first signal;  
removing power from a second set of said circuits in response to a second signal;  
indicating a time interval between an instance of said second signal and an instance of said first signal;  
determining members of said first set of circuits based upon said indication.

15.14 (currently amended) In a video display apparatus, a method for controlling an image lighting lamp circuit, the method comprising the steps of:

energizing selected circuits of said video display apparatus in response to a power on control signal;

de-energizing circuits of said video display in response to a power off control signal;

utilizing said power off control signal to start a timer;

providing an indication of a condition of said timer;

wherein said selected circuits are selected based upon said indication.